



The Model T200U NO_y Trace-Level Chemiluminescence NO/NO_y Analyzer



The Model T200U NO_y analyzer has been developed and refined specifically to address the challenges of NO_y monitoring, for example in the US NCore network. It uses the proven Chemiluminescence principle and is coupled with a remote NO_y converter via umbilical to allow measurements with a lower detectable limit of 50 ppt.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty
- Dual Sample Conditioner included



T200U NO_y Specifications

■ Ranges	Min: 0 - 5 ppb full scale Max: 0 - 2,000 ppb full scale (selectable, independent NO, NO ₂ , NO _y ranges)
■ Measurement Units	ppb, µg/m ³ (selectable)
■ Zero Noise	< 25 ppt (RMS)
■ Span Noise	< 0.5% of reading (RMS) above 5 ppb
■ Lower Detectable Limit	< 50 ppt
■ Zero Drift	< 0.1 ppb/24 hours
■ Span Drift	< 0.5% of reading/24 hours
■ Response Time	< 70 seconds to 95%
■ Linearity	1% of full scale
■ Precision	0.5% of reading above 5 ppb
■ Sample Flow Rate	1800 cc/min ±200cc/min (NO & NO _y)
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz, Typical power 110W
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	±10%
■ Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
■ Operating Temperature Range	5 - 40°C
■ Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
■ Weight	Analyzer: 40 lbs (18 kg) Converter with umbilical: 42 lbs (19.05 kg) External pump: 22 lbs (10 kg) NO _y Bypass Pump Assembly: 28 lbs (12.7 kg)

Specifications subject to change without notice.
All specifications are based on constant conditions.



TELEDYNE API
Everywhereyoulook™

9970 Carroll Canyon Road ■ San Diego, CA 92131
Ph. 858-657-9800 Fax 858-657-9816
Email api-sales@teledyne.com

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2019 Teledyne API
Printed documents are uncontrolled. SAL000050E
(DCN 8120) 07.15.19

